



LINOFOG FIX

Art. No 1800-1835

Page 1 (1)

[page 121]

FOR DAMAGES AND
NON MOVING JOINTS

Linofog Fix is a polyurethane based, 2-component material to be mixed with fine grain aggregate. Linofog Fix is developed to enable quick repairs with short open time and quick drying time of approx 2-3 hours. Linofog Fix is applied in thicknesses between 0-40 mm.

Laying instructions:

- 1.) Make sure that the surface is free from dust and moisture.
- 2.) Apply Linoprimer evenly over the surface.
- 3.) Let the Linoprimer dry for approx 3 hours (based on temperatures + 14-18°C)
- 4.) Mix 2,5 kg aggregate with 1,75 kg Linofog Fix Base. Add the 0,75 kg hardener, mix to a smooth mixture (empty the hardener can thoroughly).
- 5.) Apply the mixture with a hand trowel.
- 6.) Let it harden for approx 2 hours (based on temperatures between + 14 -18°C)
- 7.) When more aesthetic demands are required, grind the joint with a fine grain sandpaper, first after 3-4 hours after application (based on temperatures between +14-18°C)



Consumption:

1 kg ready mixed material is enough for approx 1m² and 1,8mm thickness.

Packaging:

Linofog Fix base 1,75 kg, Linofog Fix hardener 0,75 kg, Linofog Fix aggregate 2,5 kg = 1 set/5 kg = 1 m² and 9 mm thickness.

AB Lindec endeavours to provide correct information about technical properties and handling of its products. However, while AB Lindec has no control over the way in which the products are mixed and laid, or the conditions under which they set, AB Lindec can in no way be held responsible. AB Lindec is only responsible for the quality of the products at the time of delivery.