



PEDUREX

POLYURETHANE LACQUER

Pedurex polyurethane lacquer is for application on concrete floors and gives a good abrasion resistance against wear and tear. Pedurex polyurethane lacquer is a one component lacquer with very good penetration ability.

The floor must be at least 6 months old and free of moisture.

APPLICATION METHOD

Always grind the surface before treatment to achieve the best possible adhesion, and make sure that the surface is free of loose particles, grease and fat and vacuum clean it thoroughly! Apply with brush or roller.

Two treatments are recommended.

Mix Pedurex with colour paste: 10 litres Pedurex with 5 kg colour paste.

Mix the material for both treatments at the same time.

Material for second treatment should stand mixed and ready for approx 10-15 hours.

1:st treatment: Consumption: 0,15 litres/m² (lacquer 0,10 litres + colour paste 0,05 kg). Treat the surface and leave to dry.

2:nd treatment: Consumption: 0,15 litres/m² (lacquer 0,10 litres + colour paste 0,05 kg). The surface must be dry before beginning 2:nd treatment.

In case of fouling or damages, grind the surface lightly and vacuum clean before second treatment. If necessary, apply a third layer.

Material consumption / m ²	1:st treatment	2:nd treatment	Total
Pedurex	0,10 litres	0,10 litres	0,20 litres
Colour paste	0,05 kg	0,05 kg	0,10 kg

Drying time; approx 3-4 hours and the floor can be used after approx 12 hours.

Density: approx 1,0.

Finish; glossy



Volvo Construction Equipment Plant in Lindesberg, Sweden



AB Lindec endeavours to provide correct information about technical properties and handling of its products. However, while AB Lindec has no control over the way in which the products are mixed and laid, or the conditions under which they set, AB Lindec can in no way be held responsible. AB Lindec is only responsible for the quality of the products at the time of delivery.