



ProScreed

FLOATING SURFACE SCREED



Art. No 11151-11159

Page 1 (2)

[page 197]



New generation screeding with ergonomic advantages. Replaces heavy vibrating beams and unnecessary form work.

- Light weight
- Quick
- Saves money
- Increases capacity

- Non vibrating handles provide more ergonomic work and are more user friendly
- Adjustable handles provide operator with complete throttle and kill switch control, during operation



ProScreed



Placing concrete:

Place and spread the concrete as even as possible, using a preferable concrete "slump" between 15-17 cm.



Flatness:

Use laser or optical instrument to make flattest slab possible. Place the laser plate and vibrate around it. Wait for the laser signal to assure the right level on every half to one m².



Screeding:

Work across the levelled concrete in both directions to assure the best possible flatness.



Security:

For even better flatness/result, use ProScreed in one direction and an Allen channel float in the opposite direction.

11151	ProScreed 1,7Hp HO		9 kg
11155	Blade	2 m	4 kg
11156	Blade	3 m	5 kg
11157	Blade	4 m	6 kg
11158	Blade	5 m	9 kg

Shipping details:

Engine unit: 1 pc; 70x50x55cm, 14,7 kg
 Blade: 1 pc; length x 30x30cm

ab lin-pro

Box 5, Femvägsskälet 3, 421 21 V. Frölunda, Sweden
 Tfn. +46-31-69-49-10. Fax +46-31-29-88-76
 info@alleneurope.com www.concretefloor.com